



## Material Safety Data Sheet

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**PRODUCT NAME:** 82-A SERIES INLINE RESIN SPLICING KIT  
**MANUFACTURER:** 3M  
**DIVISION:** Electrical Markets Division

**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 02/03/2009  
**Supersedes Date:** 02/03/2009

**Document Group:** 08-4951-3

### ID Number(s):

80-6109-8155-9, 80-6109-8156-7, 80-6109-8157-5, 80-6109-8158-3

**This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:**

24-9848-3, 24-9869-9

### Revision Changes:

Kit: ID Number(s) was modified.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy.

In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.



## Material Safety Data Sheet

Copyright, 2008, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** SCOTCHCAST RESIN 4 PART A  
**MANUFACTURER:** 3M  
**DIVISION:** Electrical Markets Division

**ADDRESS:** 3M Center  
 St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 12/16/2008  
**Supersedes Date:** Initial Issue

**Document Group:** 24-9848-3

#### Product Use:

Intended Use: Electrical  
 Specific Use: PART A OF RESIN 4

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER	25068-38-6	80 - 100
OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL]DERIVATIVES	68609-97-2	0 - 20

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Resin

**Odor, Color, Grade:** Clear, amber resin with epoxy odor

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause allergic skin reaction.

#### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Skin Contact:**

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** No need for first aid is anticipated.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature	No Data Available
Flash Point	>= 201 °F [Test Method: Closed Cup]
Flammable Limits - LEL	No Data Available
Flammable Limits - UEL	No Data Available

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Water may be used to blanket the fire. Wear full protective equipment

(Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

**Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.**

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Avoid eye contact. Avoid skin contact. Do not ingest. Contents may be under pressure, open carefully. For industrial or professional use only.

### 7.2 STORAGE

Keep container in well-ventilated area. Keep container tightly closed. Store in a cool, dry place.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Not applicable.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Indirect Vented Goggles.

#### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Neoprene.

**8.2.3 Respiratory Protection**

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

**8.2.4 Prevention of Swallowing**

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

**8.3 EXPOSURE GUIDELINES**

None Established

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Specific Physical Form:</b>	Resin
<b>Odor, Color, Grade:</b>	Clear, amber resin with epoxy odor
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	>= 201 °F [ <i>Test Method:</i> Closed Cup]
<b>Flammable Limits - LEL</b>	<i>No Data Available</i>
<b>Flammable Limits - UEL</b>	<i>No Data Available</i>
<b>Boiling point</b>	>= 201 °F
<b>Density</b>	1.16 g/ml
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<= 27 psia [ <i>@ 131 °F</i> ]
<b>Specific Gravity</b>	1.16 [ <i>Ref Std:</i> WATER=1]
<b>pH</b>	<i>No Data Available</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Solubility In Water</b>	<i>No Data Available</i>
<b>Solubility in Water</b>	Negligible
<b>Percent volatile</b>	Negligible
<b>Viscosity</b>	3000 centipoise - 5000 centipoise

**SECTION 10: STABILITY AND REACTIVITY**

**Stability:** Stable.

**Materials and Conditions to Avoid:** None known

**Hazardous Polymerization:** Hazardous polymerization will not occur.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Cure (harden, set, or react) the product according to product instructions.

Dispose of completely cured (or polymerized) wastes in a sanitary landfill.

As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

**EPA Hazardous Waste Number (RCRA):** Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

LH-A100-0560-7, LH-A100-0560-8, LH-A100-0560-9, LH-A100-0561-0, LH-A100-0561-1, LH-A100-0561-2

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

## STATE REGULATIONS

Contact 3M for more information.

## CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

**Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health: 2 Flammability: 1 Reactivity: 0 Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

No revision information is available.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.



3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.



## Material Safety Data Sheet

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** SCOTCHCAST RESIN 4 PART B

**MANUFACTURER:** 3M

**DIVISION:** Electrical Markets Division

**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 01/07/2009

**Supersedes Date:** Initial Issue

**Document Group:** 24-9869-9

**Product Use:**

Intended Use: Electrical  
Specific Use: PART B OF RESIN 4

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
PHENOL, 4-NONYL-, branched	84852-15-3	20 - 40
HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS	64742-11-6	10 - 20
REACTION PRODUCTS	68919-79-9	10 - 20
N-AMINOETHYLPIPERAZINE	140-31-8	10 - 20
PETROLEUM DISTILLATES	Trade Secret	0 - 10
TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL	90-72-2	0 - 10
REACTION PRODUCTS WITH ETHER	Trade Secret	0 - 10
REACTION PRODUCTS WITH TETA AND DGEBA	Trade Secret	0 - 10
(2-AMINOETHYL)ETHANOLAMINE	111-41-1	0 - 5
DIETHYLENETRIAMINE	111-40-0	0 - 5
BENZ[A]ANTHRACENE	56-55-3	0 - 5
SULFUR	7704-34-9	0 - 5
BIS[(DIMETHYLAMINO)METHYL]PHENOL	71074-89-0	0 - 5
CARBON BLACK	1333-86-4	0 - 5
TRIETHYLENETETRAMINE	112-24-3	0 - 5

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Resin

**Odor, Color, Grade:** Smooth, black liquid with amine odor

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause chemical eye burns. May cause allergic skin reaction. May cause chemical skin burns. May cause chemical gastrointestinal burns. May cause allergic respiratory reaction. May cause chemical respiratory tract burns. Contains a chemical or chemicals which can cause cancer. Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Skin Contact:**

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Inhalation:**

Respiratory Tract Corrosion: Signs/symptoms may include nasal discharge, severe nose and throat pain, chest tightness and pain, coughing up blood, wheezing, and breathlessness, possibly progressing to respiratory failure.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May be absorbed following ingestion and cause target organ effects.

**Target Organ Effects:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
BENZ[A]ANTHRACENE	56-55-3	Group 2A	International Agency for Research on Cancer
BENZ[A]ANTHRACENE	56-55-3	Anticipated human carcinogen	National Toxicology Program Carcinogens

## SECTION 4: FIRST AID MEASURES

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water for at least 15 minutes. Get immediate medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. Get immediate medical attention.

**If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

<b>Flash Point</b>	$\geq 200$ °F [ <i>Test Method: Closed Cup</i> ]
<b>Flammable Limits - LEL</b>	<i>No Data Available</i>
<b>Flammable Limits - UEL</b>	<i>No Data Available</i>

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Contents may be under pressure, open carefully. Avoid breathing of vapors, mists or spray. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment.

### 7.2 STORAGE

Store away from acids. Keep container in well-ventilated area. Store away from areas where product may come into contact with food or pharmaceuticals.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers. If exhaust ventilation is not available, use appropriate respiratory protection.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Indirect Vented Goggles.

#### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber, Neoprene.

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface supplied-air respirator. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
BENZ[A]ANTHRACENE	ACGIH	TWA	No exposure	No Exposure Should be Allowed; Table A2
DIETHYLENETRIAMINE	ACGIH	TWA	1 ppm	Skin Notation*
DIETHYLENETRIAMINE	OSHA	TWA	1 ppm	Skin Notation*; Table Z-1A
TRIETHYLENETETRAMINE	AIHA	TWA	1 ppm	Skin Notation*
TRIS(2,4,6-	CMRG	TWA	5 ppm	

DIMETHYLAMINOMONOMETHYL)PHEN  
OL

\* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

**SOURCE OF EXPOSURE LIMIT DATA:**

ACGIH: American Conference of Governmental Industrial Hygienists  
 CMRG: Chemical Manufacturer Recommended Guideline  
 OSHA: Occupational Safety and Health Administration  
 AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Specific Physical Form:</b>	Resin
<b>Odor, Color, Grade:</b>	Smooth, black liquid with amine odor
<b>General Physical Form:</b>	Liquid
<b>Flash Point</b>	>= 200 °F [ <i>Test Method: Closed Cup</i> ]
<b>Flammable Limits - LEL</b>	<i>No Data Available</i>
<b>Flammable Limits - UEL</b>	<i>No Data Available</i>
<b>Boiling point</b>	>= 200 °F
<b>Density</b>	1.04 g/ml
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<= 27 psia [ <i>@ 131 °F</i> ]
<b>Specific Gravity</b>	1.04 [ <i>Ref Std: WATER=1</i> ]
<b>Solubility in Water</b>	Negligible
<b>Percent volatile</b>	3 % - 5 %
<b>Viscosity</b>	2200 centipoise - 3500 centipoise

**SECTION 10: STABILITY AND REACTIVITY**

**Stability:** Stable.

**Materials and Conditions to Avoid:** None known

**Hazardous Polymerization:** Hazardous polymerization will not occur.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Amine Compounds	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Cure (harden, set, or react) the product according to product instructions.

Dispose of completely cured (or polymerized) wastes in a sanitary landfill.

As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

**EPA Hazardous Waste Number (RCRA):** Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

LH-A100-0562-8, LH-A100-0562-9, LH-A100-0563-0, LH-A100-0563-1, LH-A100-0563-2, LH-A100-0563-3

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
BENZ[A]ANTHRACENE (Polycyclic aromatic compounds - 0.1% de minimis (EPCRA 313))	56-55-3	0 - 5

**This material contains a chemical which requires export notification under TSCA Section 12[b]:**

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
DIETHYLENETRIAMINE	111-40-0	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
PHENOL, 4-NONYL-, branched	84852-15-3	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

**STATE REGULATIONS**

Contact 3M for more information.

**CALIFORNIA PROPOSITION 65**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
BENZ[A]ANTHRACENE	56-55-3	**Carcinogen

\*\* WARNING: contains a chemical which can cause cancer.

**CHEMICAL INVENTORIES**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**INTERNATIONAL REGULATIONS**

Contact 3M for more information.

**This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: OTHER INFORMATION**

**NFPA Hazard Classification**

**Health: 3 Flammability: 1 Reactivity: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the



inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**HMIS Hazard Classification**

**Health: 3 Flammability: 1 Reactivity: 0 Protection: X** - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

No revision information is available.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.