

**CHASE PIPELINE PRODUCTS**  
**TAPECOAT® / ROYSTON® DIVISIONS OF CHASE CORPORATION**  
**MATERIAL SAFETY DATA SHEET**

**Product:** Roybond 747 Adhesive Aerosol

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**MANUFACTURED BY:** CHASE CORPORATION PITTSBURGH  
201 ZETA DRIVE  
PITTSBURGH, PA 15238

**GENERAL INFORMATION:** (412) 828-1500

**EMERGENCY, CHEMTREC:** 800-424-9300, Only in the event of chemical emergencies involving a spill, leak, fire, exposure or any accident involving chemicals. Outside USA: (703) 527-3887

**REVISION DATE:** January 20, 2010  
**PREPARED BY:** Frederick F. Fischer, Jr.

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

| <u>CAS NUMBER</u> | <u>IDENTIFICATION</u> | <u>APP. % BY WGT.</u> |
|-------------------|-----------------------|-----------------------|
| 108-88-3          | Toluene               | 10-15                 |
| 78-93-3           | Methyl Ethyl Ketone   | < 5                   |
| 999-93-3          | Hexamethyldisilazane  | < 0.5                 |
| 65996-93-2        | Coal Tar Pitch*       | < 5                   |
| 67-64-1           | Acetone               | 25-30                 |
| 1330-20-7         | Xylene                | 10-15                 |
| 100-41-4          | Ethylbenzene          | < 1                   |
| 74-98-6           | Propane               | 15-20                 |
| 106-97-8          | Butane                | 15-20                 |
| 1333-86-4         | Carbon Black          | < 5                   |

\* Listed as known Carcinogen

**3. HAZARDOUS IDENTIFICATION**

**HAZARDOUS POLYMERIZATION:** Will Not Occur

**ROUTES OF EXPOSURE:** Inhalation, Skin, Eyes and Ingestion.

**IMMEDIATE EFFECTS:**

**INHALATION:** Causes irritation of nasal passages and throat. Causes stupor (central nervous system depression).

**SKIN CONTACT:** Can cause moderate skin injury (reddening and swelling).

**EYE CONTACT:** Liquid and vapors are irritating to eyes. Can cause severe injury.

**INGESTION:** Can cause mental sluggishness.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

**ACCUTE:** Can Cause severe eye irritation, redness, tearing, and blurred vision. Excessive inhalation of vapors can cause nausea, respiratory irritation, central nervous system affects, including dizziness, weakness, fatigue, nausea, headache, and possible unconsciousness and even death. Swallowing can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis, which is fatal.

**CHASE PIPELINE PRODUCTS**  
**TAPECOAT® / ROYSTON® DIVISIONS OF CHASE CORPORATION**  
**MATERIAL SAFETY DATA SHEET**

**CHRONIC:** Prolonged and repeated skin contact can cause moderate irritation, defatting and dermatitis. Overexposure in laboratory animals has been found the cause of the following affects: Liver abnormalities, kidney damage, lung damage, and spleen damage. Overexposure to this material has been suggested as a cause for liver abnormalities in humans. Prolonged or repeated contact may lead to dermatitis, and with poor hygiene practices, to skin cancer. An Ingredient in this material has been listed as a carcinogen by IARC, NPT, QSHA, and ACGIH.

---

**4. FIRST AID MEASURES**

**GENERAL ADVICE:** Consult Physician immediately.

**INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. Move to an area free from risk of further exposure. Treat symptomatically. Administer oxygen or artificial respiration as needed. **SEEK MEDICAL ATTENTION.**

**SKIN CONTACT:** Repeated or prolonged contact can cause drying of skin and dermatitis. Remove contaminated clothing and launder thoroughly before reuse Wash affected skin thoroughly with soap and water. **DO NOT USE SOLVENTS** on skin as they may promote absorption of this material. For severe exposure, get under safety shower after removing clothing, and then **SEEK MEDICAL ATTENTION** if irritation develops or persists after the area has been washed.

**EYE CONTACT:** Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. Refer individual to a physician or ophthalmologist for immediate follow up. **SEEK MEDICAL ATTENTION.**

**INGESTION:** **DO NOT INDUCE VOMITING.** Give 1-2 cups of milk or water to drink. **DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEEK MEDICAL ATTENTION.**

---

**5. FIRE FIGHTING MEASURES**

**SUITABLE EXTINGUISHING MEDIA:** Foam, Carbon Dioxide or dry chemical. Use self-contained breathing apparatus if applicable.

**EXPLOSION DATA:**

**SENSITIVITY TO MECHANICAL IMPACT:** Stable.

**SENSITIVITY TO STATIC DISCHARGE:** Expected to be sensitive to static discharge when vapors are present between the lower and upper explosive limits.

---

**6. ACCIDENTAL RELEASE MEASURES**

**PRECAUTIONS FOR PERSONNEL:** Wear protective clothing. Use self-contained breathing apparatus if required.

**ENVIRONMENTAL PRECAUTIONS:** Avoid discharge to drains, sewers and natural water supply.

**PROCESS FOR CLEANING:** Absorb with inert material. Remove sources of ignition. Scoop material with non-sparking tools.

---

**7. HANDLING AND STORAGE**

**HANDLING:** Ventilate work area sufficiently. Keep containers closed. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store between  $-15^{\circ}\text{C}$  and  $+35^{\circ}\text{C}$  for solvent based coatings and thinners. Ground all metal containers. 55-gallon drums may be stored on their sides in a cradle designed for this purpose.

---

**CHASE PIPELINE PRODUCTS**  
**TAPECOAT® / ROYSTON® DIVISIONS OF CHASE CORPORATION**  
**MATERIAL SAFETY DATA SHEET**

**8. EXPOSURE RESTRICTIONS AND PERSONAL PROTECTION**

MATERIALS WITH LIMITS THAT REQUIRE SUPERVISION:

| <u>CAS NUMBER</u> | <u>IDENTIFICATION</u> | <u>APP. % BY WGT.</u> | <u>NIOSH REL</u> | <u>VALUE</u> | <u>UNIT</u>             |
|-------------------|-----------------------|-----------------------|------------------|--------------|-------------------------|
| 108-88-3          | Toluene               | 10-15                 | TWA              | 50           | ppm                     |
| 78-93-3           | Methyl Ethyl Ketone   | < 5                   | TWA              | 200/ 590     | ppm(mg/m <sup>3</sup> ) |
| 999-93-3          | Hexamethyldisilazane  | < 0.5                 | TWA              | 0.2          | mg/m <sup>3</sup>       |
| 65996-93-2        | Coal Tar Pitch*       | < 5                   | TWA              | 0.2          | mg/m <sup>3</sup>       |
| 67-64-1           | Acetone               | 25-30                 | TWA              | 750          | ppm                     |
| 1330-20-7         | Xylene                | 10-15                 | TWA              | 100          | ppm                     |
| 100-41-4          | Ethylbenzene          | < 1                   | TWA              | 100          | ppm                     |
| 74-98-6           | Propane               | 15-20                 | TWA              | 1000         | ppm                     |
| 106-97-8          | Butane                | 15-20                 | TWA              | 800          | ppm                     |
| 1333-86-4         | Carbon Black          | < 5                   | TWA              | 3.5          | mg/m <sup>3</sup>       |

ADDITIONAL ADVICE: Use personal protective equipment, i.e., suitable work clothing, eye goggles and protective gloves. If spraying utilize protective facemask.

**9. PHYSICAL PROPERTIES**

ODOR: AROMATIC

| <u>CHANGE OF STATE</u> | <u>VALUE/AREA</u>      | <u>UNIT</u>          | <u>METHOD</u> |
|------------------------|------------------------|----------------------|---------------|
| FREEZING POINT:        | N/A                    | °C                   |               |
| BOILING POINT:         | -17.78 -114.5 (0-238)  | °C (°F)              |               |
| FLASH POINT:           | -17.78 ( 0) Propellant | °C (°F)              |               |
| IGNITION TEMPERATURE:  |                        |                      |               |
| SPECIFIC GRAVITY:      | 0.75                   | H <sub>2</sub> O = 1 |               |
| % VOLATILE BY VOLUME:  | 85-95                  | %                    |               |
| SOLUBILITY IN WATER:   | NEGLIGIBLE             |                      |               |
| PH VALUE:              | N/A                    |                      |               |
| VISCOSITY:             |                        | CPS                  |               |
| FLAMMABLE LIMITS:      | LEL 1.0 UEL 12.8       |                      |               |
| EVAPORATION RATE:      | Faster than ether      | BUAC = 1             |               |

**10. STABILITY AND REACTIVITY**

STABILITY: Stable

CONDITIONS TO AVOID: Sparks and Open Flame.

MATERIALS TO AVOID: Contact with strong oxidizing, acidic or alkaline agents.

DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen.

EYES: Splashes or spray vapors may cause irritation.

SKIN: Substance may be an irritant for sensitive skin.

INHALATION: May cause mild nausea/dizziness in some people when used in confined/unventilated areas. Move patient to fresh air. Give nothing by mouth.

CONSUMPTION: If accidentally swallowed may cause discomfort and requires plenty of water or milk to dilute. Do not induce vomiting. Seek medical assistance.

**CHASE PIPELINE PRODUCTS**  
**TAPECOAT® / ROYSTON® DIVISIONS OF CHASE CORPORATION**  
**MATERIAL SAFETY DATA SHEET**

**11. TOXICOLOGICAL INFORMATION**

| <u>CAS NUMBER</u> | <u>IDENTIFICATION</u> | <u>DERMAL LD50</u>      | <u>INAHALATION LC50</u>           | <u>ORAL LD50</u>                   |
|-------------------|-----------------------|-------------------------|-----------------------------------|------------------------------------|
| 108-88-3          | Toluene               | 12.3 g/kg ( rabbit )    | 4959 ppm ( Rat )                  | 7.0 g/kg ( Rat )                   |
| 78-93-3           | Methyl Ethyl Ketone   | 6,480 mg/kg ( Rabbit )  | 23,500 mg/m <sup>3</sup> ( Rat )  | 2,740 mg/kg ( Rat )                |
| 999-93-3          | Hexamethyldisilazane  | 710 µl/kg (Rat)         | 8,700 mg/m <sup>3</sup> /4H (Rat) | 850 mg/m <sup>3</sup> ( Rat )      |
| 65996-93-2        | Coal Tar Pitch*       | N/E                     | 17 mg/m <sup>3</sup> ( Rat )      | 6,200 mg/kg ( Rat )                |
| 67-64-1           | Acetone               | 9400 g/kg (Guinea Pig ) | 50,100 mg/ M <sup>3</sup> / 8H    | 5,340 mg/M <sup>3</sup> ( Rabbit ) |
| 1330-20-7         | Xylene                | 12.2g/kg ( Rabbit )     | 4,550 ppm ( Rat )                 | 4.3g/kg ( Rat )                    |
| 100-41-4          | Ethylbenzene          | 15.4 g/kg ( Rabbit )    | 2,624 mg/m <sup>3</sup> ( Rat )   | 3.5 mg/kg ( Rat )                  |
| 74-98-6           | Propane               | N/E                     | N/E                               | N/E                                |
| 106-97-8          | Butane                | N/E                     | N/E                               | N/E                                |
| 1333-86-4         | Carbon Black          | N/E                     | 27,000 mg/M <sup>3</sup> ( Rat )  | > 8,000 mg/kg ( Rat )              |

| <u>CAS NUMBER</u> | <u>IDENTIFICATION</u> | <u>CARCINOGENICITY</u> |             | <u>TERATOGENICITY</u> | <u>MUTAGENICITY</u> |
|-------------------|-----------------------|------------------------|-------------|-----------------------|---------------------|
|                   |                       | <u>ACGIH</u>           | <u>IARC</u> |                       |                     |
| 108-88-3          | Toluene               | N/E                    | N/E         | Yes                   | N/E                 |
| 78-93-3           | Methyl Ethyl Ketone   | N/E                    | N/E         | N/E                   | N/E                 |
| 999-93-3          | Hexamethyldisilazane  | N/E                    | N/E         | N/E                   | N/E                 |
| 65996-93-2        | Coal Tar Pitch*       | Yes                    | Yes 2 B     | N/E                   | Yes                 |
| 67-64-1           | Acetone               | N/E                    | N/E         | N/E                   | N/E                 |
| 1330-20-7         | Xylene                | N/E                    | N/E         | N/E                   | N/E                 |
| 100-41-4          | Ethylbenzene          | Yes                    | Yes 2 B     | N/E                   | N/E                 |
| 74-98-6           | Propane               | N/E                    | N/E         | N/E                   | N/E                 |
| 106-97-8          | Butane                | N/E                    | N/E         | N/E                   | N/E                 |
| 1333-86-4         | Carbon Black          | Yes                    | Yes 2 B     | Yes                   | N/E                 |

**12. ECOLOGICAL INFORMATION**

VOLATILE ORGANIC COMPOUNDS: 624 Grams Per Liter (g/l). 5.29 Pounds Per Gallon (lb/g).

**13. DISPOSAL CONSIDERATIONS**

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State and Local regulations.

**14. TRANSPORT INFORMATION**

|                      |                     |                   |                    |
|----------------------|---------------------|-------------------|--------------------|
| SHIPPING             | AIR                 | OCEAN             | TRUCK              |
| Proper Shipping Name | AEROSOLS, FLAMMABLE | AEROSOLS          | CONSUMER COMMODITY |
| Hazardous Code       |                     |                   |                    |
| UN Number            | UN 1950             | UN 1950           | None               |
| IMDG Page:           |                     | 2102, LTD QTY 910 |                    |

**CHASE PIPELINE PRODUCTS**  
**TAPECOAT<sup>®</sup> / ROYSTON<sup>®</sup> DIVISIONS OF CHASE CORPORATION**  
**MATERIAL SAFETY DATA SHEET**

|                 |               |                                |                                |
|-----------------|---------------|--------------------------------|--------------------------------|
| Outer Packaging | 15 KG         | STRONG INDUSTRIAL<br>PACKAGING | STRONG INDUSTRIAL<br>PACKAGING |
| Markings        |               |                                | MARK ON PACKAGE<br>OMR-D       |
| Label           | FLAMMABLE GAS | NO LABEL                       | NO LABEL                       |

---

**15. REGULATORY INFORMATION**

SARA SECTION 302:

SARA (311,312) HAZARD CLASS:

SARA (313) CHEMICALS: TOLUENE, XYLENE , ACETONE,

CERCLA: Toluene: 1000 LBS.XYLENE: 1000 LBS.

CPSC CLASSIFICATION:

HMIS: FLAMMABILITY: 3      REACTIVITY: 0      HEALTH: 2

NFPA: FLAMMABILITY: 3      REACTIVITY: 0      HEALTH: 2

CALIFORNIA PROPOSITION 65:

- A. This product contains a chemical known to the State of CA to cause birth defects or other reproductive harm.
- B. This product contains a chemical known to the State of CA to cause cancer.
- C. This product contains a chemical known to the State of CA to cause cancer and birth defects or other reproductive harm.

---

**16. OTHER INFORMATION**

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND ARE NOT A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED IS MADE. THE STATED RECOMMENDED HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE.

C = Ceiling Limit, NEGL = Negligible, N/A = Not Applicable, N/E = Not Established, PROP. = Proprietary.

---