

PSI LineSeal™ Flange Isolation Ordering Guide/Worksheet

Quantity	Nominal Pipe Size	ANSI Class	Gasket Type	Gasket Style	For LineSeal™ Sealing Gaskets		Washers	Washer Material	Sleeve	Gasket I.D. Schedule Pipe Flange	Type
Specify Below	Specify Below	150# 300# 400# 600# 900# 1500# 2500#	E = With Bolt Holes F = Ring (No Bolt Holes)	LS = LineSeal	Retainer G-10 G-11	Seal Element Viton Teflon Nitrile	SW = Single Washers DW = Double Washers	G-10 1 PC G-10 G-11	Mylar G-10 G-11	Specify Below	W = Weld Neck S = Slip On R = RTJ BX = API BX RX = API RX O = Other Denote Specs. and Table

Quantity	Nominal Pipe Size	ANSI Class	Gasket Type	Gasket Style	For LineSeal™ Sealing Gaskets		Washers	Washer Material	Sleeve	Gasket I.D. Schedule Pipe Flange	Type
					Retainer	Seal Element					



For Flange Isolation Kits over 24" in addition to the above please specify:

Flange Facing <i>(Raised, RTJ..etc)</i>	_____	Nominal Bolt Diameter <i>(Threads/Inch)</i>	_____
Flange I.D.	_____	Sleeve Length	_____
Flange O.D.	_____	Pipe I.D.	_____
Flange Thickness	_____	Steel Sleeve I.D. <i>(For Concrete Pipe)</i>	_____
Number of Studs/Bolts	_____	Product In Line	_____
Stud/Bolt Diameter	_____	AWWA Class & Table <i>(Or other similar std.)</i>	_____
Stud/Bolt Hole Diameter	_____	Internal Lining	_____
Stud/Bolt Circle Diameter	_____		

Flange Faces >250 Micro Inches: For flange face surfacing greater than 250 micro inches, consult factory.

Note: Caution! Bolts with smooth shank portions may not fit within sleeves. Verify prior to ordering.

