



Material Safety Data Sheet

DATE: 5/15/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name	PROTAL 7900HT PART B HARDENER
Product Use Description	Curing Agent Epoxy
Manufacturer / Importer/ Distributor	Denso North America 9747 Whithorn Drive Houston, Texas 77095 281-821-3355 (Office) 281-821-0304 (Fax)
Telephone	1-281-821-3355 Corporate 1-888-821-2300 Toll Free Number
Emergency Telephone Number (24Hour)	1-801-629-0667

2. HAZARDS IDENTIFICATION

Emergency Overview	WARNING! Corrosive. Irritant. Toxic in contact with skin. Harmful if inhaled or swallowed. Severe respiratory irritant. Severe skin irritant. Severe eye irritant. May cause sensitization by skin contact. This product is hazardous according to OSHA 29 CFR 1910.1200.
Potential Health Effects	
Inhalation	Can cause severe eye, skin and respiratory tract burns. May cause nose, throat, and lung irritation. Inhalation of vapors and / or aerosols in high concentration may cause irritation of respiratory system.
Ingestion	Harmful, if swallowed. If ingested, may cause severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.
Eye contact	Causes eye burns. May cause blindness. Severe eye irritation.
Skin contact	Toxic in contact with skin. Causes skin burns.
Target Organs	Skin. Eyes. Respiratory system. Gastrointestinal tract.
Chronic Health Hazard	This product contains no listed carcinogens according to IARC, ACGIH, NTP and / or OSHA in concentrations of 0.1 percent or greater. Prolonged contact may result in chemical burns and permanent damage. Repeated or prolonged contact causes sensitization, asthma and eczemas.
Potential Environmental Effects	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Aggravated Medical Condition	Eye disease, Skin disorders and Allergies. Asthma.
See section 11 for more detailed toxicological information	

Material Safety Data Sheet

DATE: 5/15/2013

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration
4,4'-Methylenebiscyclohexanamine	1761-71-3	40-50%
Methyleneoxide, polymer with benzeneamine, hydrogenated	135108-88-2	5-10%

CHEMICAL FAMILY : Cycloaliphatic Amine mixture.

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. FIRST AID MEASURES

General advice	Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.
Eye contact	Check for and remove any contact lenses. Hold eyelids apart, initiate and maintain gentle and continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour. Rinse immediately with plenty of water also under the eyelids for at least 20 minutes.
Skin contact	Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay. Initiate and maintain gentle and continuous irrigation until the patient receives medical care. If medical care is not promptly available, continue to irrigate for one hour. Cover wound with sterile dressing. Take off contaminated clothing and shoes immediately. NOTE TO PHYSICIANS: Application of corticosteroid cream has been effective in treating skin irritation.
Ingestion	Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Prevent aspiration of vomit. Turn victim's head to the side.
Inhalation	If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Move to fresh air.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Alcohol-resistant foam. Carbon dioxide (CO ₂) Dry chemical. Dry sand. Limestone powder.
Hazardous Combustion Products	May generate ammonia gas. May generate toxic nitrogen oxide gases. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. Incomplete combustion may form carbon monoxide. Downwind personnel must be evacuated. Burning produces noxious and toxic fumes.
Special protective equipment for fire-fighters	Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear self contained breathing apparatus for fire fighting if necessary.
Further information	Do not allow run-off from fire fighting to enter drains or water courses.

Material Safety Data Sheet

DATE: 5/15/2013

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas. See Section 8 for Personal Protective Equipment.
Environmental precautions	Construct a dike to prevent spreading. Avoid discharge into drains, water courses, or onto the ground.
Methods for cleaning up	Approach suspected leak areas with caution. Contact Denso's Emergency Response Center (see Section 1) for advice. Cover with inert, absorbent material and place in appropriate waste container for disposal.
Additional advice	If possible, stop flow of product. Clean up in accordance with all applicable regulations.

7. HANDLING AND STORAGE

Handling	Avoid contact with skin and eyes. Emergency showers and eye wash situations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid vapors and/or aerosols. Avoid contact with eyes. Use only in well-ventilated areas. Use personal protective equipment. When using, do not eat drink or smoke. Change contaminated clothing.
Storage	Store in steel containers preferably located outdoors, above ground, and surrounded by dikes to contain spills or leaks. Keep containers tightly closed in dry, cool and well-ventilated place. Do not store near incompatible materials (See Section 10).
Technical Precautions	Do not store in reactive metal containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Recommended Monitoring	Consult with local authorities for acceptable exposure limits.
Engineering measures	Provide readily accessible eye wash stations and safety showers. Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.
Personal Protective Equipment	
Hand Protection	Wear impervious gloves to prevent any possibility of skin contact. The breakthrough time of the selected glove(s) must be greater than the intended use period. Frequent glove changes are recommended.
Eye Protection	Wear approved safety glasses or goggles to prevent any possibility of eye contact. Wear a full-face shield as well when appropriate.
Skin and Body Protection	Wear impervious clothing and footwear to prevent any possibility of skin contact. The breakthrough time of the selected clothing and footwear must be greater than the intended use period. Change contaminated clothing and footwear immediately.
Respiratory Protection	In case of inadequate ventilation, use suitable respiratory equipment with a filter for organic vapors. Change filters regularly.
Environmental Exposure controls	Construct a dike or other barrier to prevent spreading.



Material Safety Data Sheet

DATE: 5/15/2013

Special Instructions for protection and hygiene

Discard contaminated leather articles. Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Provide readily accessible eye wash stations and safety showers. Wash at the end of each work shift and before eating, smoking or using the toilet. Provide readily accessible eye wash stations and safety showers.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Viscous Liquid.	Auto-ignition temperature	N/A
Color	Black.	Odor threshold	N/A
Odor	Irritating. Amine.	Evaporation rate	N/A
Flammable limits	N/A	Viscosity	90,000 cP @ 73oF (22oC)
Relative vapor density	N/A	pH	>9
Relative Density	1.43	Boiling point/range	N/A
Vapor Pressure	N/A	Flash point	N/A
Density at 70°F (21°C)	11.9 lbs/gal	Water solubility	Slight

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Materials to avoid	Strong oxidizing agents. Strong acids. Reactive organometallic compounds. Product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion.
Other hazards	Reacts with considerable heat release with some epoxy resins.
Hazardous decomposition products	Decomposition products may include the following materials: Nitric acid. Ammonia. Nitrogen oxides (NOx). Nitrogen oxide can react with water vapors to form corrosive nitric acid. Carbon monoxide. Carbon dioxide.

11. TOXICOLOGICAL INFORMATION

Toxicological Data

Acute toxicity ingredient name	CAS #	LD50 Oral - Rat mg/kg	LD50 Dermal - Rabbit mg/kg
4,4'-Methylenebiscyclohexanamine	1761-71-3	>500	>2000

Acute Health Hazards
Epidemiology

Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure.

Material Safety Data Sheet

DATE: 5/15/2013

Eye irritation/corrosion	Severe eye irritation.
Skin irritation/corrosion	Severe skin irritation.
Sensitization	May cause sensitization by skin contact.
Respiratory irritation/corrosion	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause irritation and malaise.
Chronic Health Hazards	May cause damage to the liver and kidneys. No data is available regarding carcinogenicity, mutagenicity, or reproductive effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects	
Aquatic toxicity	No data is available on the product itself. Expected to be harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
Toxicity to other organisms	No data available.
Persistence and degradability	
Biodegradability	No data is available on the product itself.
Mobility	No data available.
Bioaccumulation	No data is available on the product itself.

13. DISPOSAL CONSIDERATIONS

Waste disposal	The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional and local authority requirements. Avoid disposal of spilled material and runoff and contact with soil, waterways, drains and sewers. Dispose of contaminated containers, soils, etc. in compliance with the requirements of environmental protection and waste disposal legislation and any regional and local authority requirements. This material and/or its container must be disposed of as hazardous waste.
----------------	---

14. TRANSPORT INFORMATION

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation. For complete transportation information, contact an Denso customer service representative.

Regulatory Information	UN/ID No.	Proper shipping name	Class or Division Packing group	Reportable Quantities
CFR	UN2735	AMINES, LIQUID, CORROSIVE, N.O.S. (Cycloaliphatic amine)	Class 8, PG III	N/A
TDG	UN2735	AMINES, LIQUID, CORROSIVE, N.O.S. (Cycloaliphatic amine)	Class 8, PG III	N/A
IMO/IMDG	UN2735	AMINES, LIQUID, CORROSIVE, N.O.S. (Cycloaliphatic amine)	Class 8, PG III	N/A
IATA	UN2735	AMINES, LIQUID, CORROSIVE, N.O.S. (Cycloaliphatic amine)	Class 8, PG III	N/A

Material Safety Data Sheet

DATE: 5/15/2013

15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) 12(b) Component(s).

None.

OSHA Hazard Communication Standard (29 CFR 1910.1 200) Hazard Class(es)

Corrosive. Sensitizer.

Country	Regulatory List	Notification
USA	TSCA	Included on Inventory.
Canada	DSL	Included on Inventory.
EU	EINECS	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

HCS Classification Corrosive material, Sensitizing material

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification

Acute Health Hazard

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level

None.

EPA SARA Title III Section 302 Extremely Hazardous Substances

None.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

WHMIS Hazard

Classification (Canada) Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists Canadian NPRI: None.

16. OTHER INFORMATION

HMIS[®]

Health	3
Flammability	1
Physical hazard	0

Caution: HMIS[®] ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS[®] ratings are not required on MSDS's under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS[®] ratings are to be used with a fully implemented HMIS[®] program. HMIS[®] is a registered mark of the National Paint & Coatings Association (NPCA). HMIS[®] materials may be purchased exclusively from J.J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

Prepared by Denso EH & S Department

Telephone 1-281-821-3355 Corporate
1-801-629-0667 Emergency (24 hour)

Date of Issue 15-May-13

Date of Printing 15-May-13

Version 1

Notice to reader

The information provided herein was believed by Denso North America ("Denso") to be accurate at the time of preparation of prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Denso are subject to Denso's terms and conditions of sale. DENSO MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY DENSO, except that the product shall conform to Denso's specifications. Nothing contained herein constitutes an offer for the sale of any product.